

EZY Palletizing System



Features:

- Fully automatic operation, simple user-programmable interface
- Provides gentle, low pressure, high friction product handling
- Integrated case handling and pattern forming conveyor
- Reliable pneumatics means very low maintenance requirements
- Variety of pallet handling systems available, including stand, lift and conveyor

Barry-Wehmiller

ACCRAPLY

Barry-Wehmiller
Company



pneumatic
SCALE ANGELUS

Thiele
Technologies

DESIGN GROUP

Barry-Wehmiller
International Resources

HayssenSandiacre

MarquipWardUnited

FleetwoodGoldcoWyard

EZY Palletizing System

The Benefits Really Stack Up:

As a world leader in product handling technology, FleetwoodGoldcoWyard offers a full line of automatic palletizing equipment to help customers increase production and cut operating costs.

The EZY Palletizer is the most economical palletizer on the market and the best way to automate production lines. This fully automated machine requires no operator, handles multiple packages, requires minimal maintenance, and has a very fast ROI. It is designed to fit in a small space and incorporates a robust design to ensure trouble free operation.


The experienced teams at FleetwoodGoldcoWyard offer a range of pallet handling systems, palletizers and depalletizers, as well as complete system design and engineering services.

SPECIFICATIONS (approximate)


Length	Overall 7'-7" (2311 mm) not including pallet conveyors
Width	
A&B Layouts	10'-0" (3048 mm) not including pallet conveyors
C&D Layouts	11'-4" (3454 mm) not including pallet conveyors
Height	11'-7" (3531 mm) standard
Load Height	86" max. (2184 mm) including pallet on 14.5" (368 mm) conveyor elevation (Optional load heights available)
Case Infeed Elevation	20" (508 mm)
Material Handled	Rectangular and square cases (standard)
Payload	200 lbs. (91 kg)
Clamping Device (hand)	Row pick
Handling Rate	Average throughput = No. of cases/row x 3.0 cycles/min.
Case Size	24"H x 24" W x 48"L (610 mm x 610 mm x 1219 mm) max. 4"H x 6" H x 6" L (102 mm x 152 mm x 152mm) min.
Ambient Temperature	32° - 100° F (0° - 38° C)
Electrical Requirements	460V, 3 phase, 60 HZ (10 amps) standard. Electrical changes optional.
Air Requirements	3 SCFM, 80 psi (.085 mΔ/min., 6.7 kg/cm ²)
Estimated Weight	3000 lbs (1361 kg) palletizer and infeed conveyor

Note: Specifications and dimensions shown are for a standard machine.


Contact us for additional information. Specifications subject to change without notice.




Layout "A"



Layout "B"



Layout "C"



Layout "D"

FleetwoodGoldcoWyard

1305 Lakeview Drive • Romeoville, IL 60446 • 630/759-6800

• **Loveland, CO**
970/663-4770

• **Lino Lakes, MN**
651/464-4000

• **St. Albans, England**
+44 1727 836101

• **Doncaster, England**
+44 1302 711056

• **Hunt Valley, MD**
410/785-1934

• **Lynchburg, VA**
434/582-1200

www.FGWA.com • sales@FGWA.com